



SPECIFICATIONS

Voltage rating: AC 250V
Current rating: AC,DC,2A
Withstand voltage: AC 800 V/min.
Insulation resistance: 1000M Ω min.
Temperature range: -25°C~+85°C
Applicable PC board thickness: 0.8~1.6mm
Contact resistance: Initial value/10 m Ω max.
After environmental
Testing/20 m Ω max.

Poles	Dimension in. (mm)		
	A	B	C
2	0.098(2.5)	0.217(5.5)	0.315(8.0)
3	0.197(5.0)	0.315(8.0)	0.413(10.5)
4	0.295(7.5)	0.402(10.5)	0.517(13.0)
5	0.394(10.0)	0.512(13.0)	0.610(15.5)
6	0.492(12.5)	0.610(15.5)	0.709(18.0)
7	0.591(15.0)	0.709(18.0)	0.807(20.5)
8	0.689(17.5)	0.807(20.5)	0.906(23.0)
9	0.787(20.0)	0.906(23.0)	1.004(25.5)
10	0.886(22.5)	1.004(25.5)	1.102(28.0)
11	0.984(25.0)	1.102(28.0)	1.201(30.5)
12	1.083(27.5)	1.201(30.5)	1.299(33.0)
18	1.673(42.5)	1.791(45.5)	1.890(48.0)

ECN NO.:									
FILE PATH:D:\pec\rf\clipart									
			SCALE	4 : 1	SHEET		1 OF 1		
			DRAWN BY: KAN			UNIT	mm	REV	A
			APPROVED BY:			DRAW NO.			
			GENERAL TOLERANCE:						
			ANGLE:	DIM:	TITLE:				
A	NEW RELEASE	05.03.07	±30'	X.X ± 0.25	WIRE TO WIRE CONNECTOR				
REV	REVISION RECORD	DATE		X.XX ± 0.15					
				X.XXX ± 0.05					