


RECOMMENDED P.C. BOARD HOLE DIMM.

Specifications

Electrical

Voltage Rating: 100V(AC)

Current Rating: 2A

Contact Resistance: 20mΩ max.

Dielectric Withstandeig Voltage: 800V AC/1min.

Insulation Resistance: 1000MΩ min.

Material

Circuits: 2~16

Insulator: Nylon 66 UL 94V-0

Color: White or Natural



Contact: Brass 0.50mm(0.20") Square Pin

Plating: Tin or Gold Plated

Temperature Range: -25° C~+85° C

Applicable PC Board Thickness: 0.8 to 1.6mm

Poles	Dimension mm (in.)	
	A	B
2	2.0(0.079)	6.04(0.237)
3	4.0(0.157)	8.04(0.316)
4	6.0(0.236)	10.04(0.395)
5	8.0(0.315)	12.04(0.473)
6	10.0(0.394)	14.06(0.473)
7	12.0(0.472)	16.06(0.631)
8	14.0(0.551)	18.08(0.711)
9	16.0(0.630)	20.08(0.790)
10	18.0(0.709)	22.10(0.870)
11	20.0(0.787)	24.10(0.949)
12	22.0(0.886)	26.12(1.027)
13	24.0(0.945)	28.12(1.106)
14	26.0(1.024)	30.14(1.203)
15	28.0(1.102)	32.14(1.283)
16	30.0(1.181)	34.14(1.363)



純通有限公司
Mindwaves Co.,Ltd

MODEL

PAGE 1 OF 1

COMPUTER NO.

UNIT

SCALE

PART NAME

mm

Wire to Board
Wafer 2.0PH 90D

APPD.

CKD.

DWG.

DATE

TOLERANCE

PART NO.

REV.

Y.J.Lin

2010.7.27

±0.3

5500__R(200PH)-GP

A